



**MATERIAL:**

- SV BODY: MANGANESE BRONZE or 416 SS
- HOUSING: CARBON STEEL
- HANDLE, DETENT & SPACERS: PLATED CARBON STEEL
- SHAFT: 416 SS
- SHEARFLO SEALING COMPONENTS: 440c HARDENED
- O-RINGS: BUNA (NITRILE)
- BACKUPS: TEFLON

**MODEL NO: SV-25 2N6ISS1MN**

ROTOR: Selector

ALL PORTS: 1/4" NPT

WORKING PRESSURE: 6000 PSI

Cv: .95

Flow (GPM): 10

Temperature Rating: -30° TO 180°F

**PacSeal HYDRAULICS INC.**

VALVES, ACCUMULATORS, CONTROLS

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PacSeal Hydraulics. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PacSeal Hydraulics IS PROHIBITED.

TITLE

SV-25/6 K Selector

SIZE

**A**

DWG. NO.

**40-1925**

REV

**2**

SCALE: 1:2

WEIGHT: 4.4

SHEET 1 OF 2

